





Smart Controller Catalog / Power Supply

※ Please click on model name for specifications

Smart Controller	Picture	Corresponding Models	Key Features
<u>CMU1</u>		<u>RCP-1000/1000-C series</u> <u>RCP-1600 series</u> <u>RCB-1600 series</u> <u>RCP-2000 series</u>	<ul style="list-style-type: none"> • 1U 19-inch rackmount and standalone • Front panel LDC and web UI • UES, RS-232 or ethernet interface for PC connection • Alarm/event log with time and data • Windows-based PC software • 4 programmable relay outputs • 5years warranty
<u>CMU2</u>		<u>DRP-3200 series</u> <u>DBR-3200 series</u> <u>NCP-3200 series</u> <u>SHP-30K series</u> <u>NTN-5K series</u> NEW	<ul style="list-style-type: none"> • 3U 19-inch rackmount and standalone • 7" TFT LCD touch panel and buttons • Ethernet port for on-site and remote operation • Selectable PMBus, CANBus, RS485, and RS-232 interface • Power management/ Burn-in/EV charging/UPS firmware ready. • Data/event log with time and date • 4 programmable relay outputs • 5 years warranty
<u>CMU3</u>	<p>COMING SOON</p> 	<u>DRP-3200 series</u> <u>DBR-3200 series</u> <u>NCP-3200 series</u> <u>SHP-30K series</u> <u>NTN-5K series</u> NEW	<ul style="list-style-type: none"> • No control panel design, connect to a smart phone via Bluetooth, Wi-Fi, and operate devices through the APP interface • Supports multi-application system data integration, consolidating data into the APP interface for control, applicable to inverter, power supply, and PV applications. • Supports multiple network protocols, including MODBus TCP, Web API, and Matter

Smart Controller Catalog / Lighting

※ Please click on model name for specifications

Smart Controller	Picture	Type	Key Features
<u>DLC-02</u>		LED driver with DALI	<ul style="list-style-type: none">• Comply with IEC 62386 DALI-2, and Part 101/103/207/208/301/302/303/304• 2 x channels of DALI bus, for control gear and control device using• 4 x programmable relays, for electrical switch or curtains control• DLC software for system settings or remotely through internet• Built-in LCD display and control buttons to set and view settings• Built-in timer IC, commission schedule• Communication interface: RJ-45 for connection expansion with other building automation systems• DIN-Rail mounting, compact design 8SU width (144x 90x 58.4mm)

Roadmap

Applications

Intelligent Lighting Control

Power Control

Burn-in System

